Other related solutions Wood screw VGZ 7x120 Rothoblaas VGZ 7120 full threaded, c/c 50 mm 0 o O o **0 0** 0 0 0 0 0 0 o • 0 0 0 0 0 WHT PLATE 600x91 0 0 0 0 0 0 0 0 Rothoblaas WHTPT600 0 0 0 0 0 o • 0

CLT PANEL

II. The structural interface details are so-called indicative general cross sections, they do not take a position on e.g. fastenings, structural strengths, etc.

Site-specific solutions and structure types are always determined by the sites structural designer according to the sites requirements. The exact dimensions of the structural layers and the performance values of the structural layers are determined in the structure layers. Variables depending on the dimensions and performance of the structural layers are:

III. Fasteners only according to the engineering project.

Wood screw HBSPL 880 Rothoblaas HBSPL880

Wood screw VGZ 11x500 Rothoblaas VGZ 11500 full threaded, x2

pan head, x30

-Building physical functioning of the structure
-Building physical functioning of the structure as whole + water vapour permeability, air tightness, thermal conductivity, weather resistance of the materials
-Achievable level of thermal insulation
-Fire compartment ability (El) and fire endurance (R) of the structure
-Fire resistance class of the materials (inflammability, snoke development, flammable drops)
-Fire resistance so of the surface layers of the structure for the background structure in the event of a fire
-Sound insulation level of the structure against traffic and aircraft noise



Property and copyright belong exclusively to the CLT FACTORY group of companies.

These drawings contain standard solutions designed by KLIK-KLIK for AutoCAD software. ese drawings are intended for architects and structural engineers to use the KLIK-KLIK Wall System..